

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 September 2003 (12.09.2003)


PCT

(10) International Publication Number  
**WO 03/074163 A1**

- (51) International Patent Classification<sup>7</sup>: **B01F 3/04**, 7/16
- (21) International Application Number: **PCT/CA03/00292**
- (22) International Filing Date: **3 March 2003 (03.03.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/361,281                      4 March 2002 (04.03.2002)    **US**
- (71) Applicant (for all designated States except US): **CYMAT CORP.** [CA/CA]; 6320-2 Danville Road, Mississauga, Ontario L5T 2L7 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **NICHOL, Scott** [CA/CA]; 2 Elma Street, Etobicoke, Ontario M8V 1X8 (CA). **MANLEY, Richard, G.** [CA/CA]; 5 Golden Gate Drive, Brampton, Ontario L6S 2K5 (CA).
- (74) Agents: **CHARI, Santosh, K.** et al.; McCarthy Tetraault LLP, Suite 4700, P.O. Box 48, 66 Wellington Street West, Toronto-Dominion Bank Tower, Toronto, Ontario M5K 1E6 (CA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: **SEALED IMPELLER FOR PRODUCING METAL FOAM AND SYSTEM AND METHOD THEREFOR**



(57) Abstract: A system for producing a metal foam comprises a bath containing a molten metal, a rotating shaft or impeller extending through the base of the bath into, and submerged in the molten metal, and a gas discharge nozzle provided on the submerged end of the shaft. The opposite end of the shaft is connected to a gas supply line and the shaft is rotated with a motor. A seal is provided at the opening in the base of the bath for preventing leakage of the molten metal there-through.

WO 03/074163 A1



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**SEALED IMPELLER FOR PRODUCING METAL FOAM  
AND SYSTEM AND METHOD THEREFOR**

**BACKGROUND OF THE INVENTION**

**FIELD OF THE INVENTION**

[0001] The present invention relates generally to submerged impellers and, more particularly, to impellers used in generating metal foam.

**DESCRIPTION OF THE PRIOR ART**

[0002] There is a considerable demand for materials having high strength and low weight characteristics for use in manufacturing various articles. Such materials are very much in demand in the automobile and construction industries. To meet this demand, metal foam has been proposed. Metal foam is generally formed by introducing a gas into a molten metal bath to generate a foam on the surface thereof. Due to its high strength to weight ratio, aluminum is a favoured metal to use in generating a foam, although other metals can also be used. The foam is then removed and formed or cast into the desired shapes. Various methods have been proposed for introducing the gas into the molten metal bath. Such methods include the use of gas generating additives, blowing of air etc. With regard to the latter method, various apparatus and systems are known for blowing a gas into the molten metal. Such apparatus include nozzles, impellers and other such devices.

[0003] In US patent number 5,334,236, there is described a metal foam generating system wherein air is introduced by means of a gas nozzle at the end of a supply tube or a hollow rotating impeller having a plurality of openings through which the gas is passed. In both cases, the tube or impeller is mounted on an angle into the metal bath through an opening. There is no teaching in this patent as to how such opening is sealed to prevent the molten metal from leaking. Further, the shafts used in forming the tubes or impellers are formed from stainless steel due to the fact that they are immersed in molten metal. Nevertheless, such shafts are known to become deteriorated after prolonged immersion in the molten metal and must be replaced often. Another deficiency in these known gas introduction systems is that since the shafts are provided in an angled manner into the molten metal bath, the length

1 of the shafts must be adjusted if the depth of the bath is increased. Apart from the drive  
2 mechanism requirements of such an arrangement, it will be understood that the cost for each  
3 shaft would also be greater. This, compounded with the need for constant replacement of the  
4 shafts, results in a high cost of operation.

5  
6 [0004] In US application number 60/312,757, sharing a common inventor with the  
7 present application, an improved metal foam generating and casting system is provided. In  
8 this system, a metal foam is generated by introducing a gas into the bottom of the metal bath  
9 to generate bubbles. The bubbles are then allowed to rise through a riser tube connected to a  
10 die cavity. The bubbles then form a foam inside the cavity. After the cavity is filled, it is  
11 allowed to cool and the formed metal foam article is retrieved. In this case, the generation of  
12 bubbles at a specific location is desired. This reference provides a porous nozzle located at  
13 the bottom of the molten metal bath, positioned generally directly under the riser tube.  
14 Although such porous nozzle results in the desired foam generation, a rotating nozzle is  
15 believed to improve the foam characteristics. However, the rotating nozzle shafts known in  
16 the art have various disadvantages as described above. In this specific application, one other  
17 disadvantage is that, with angled impeller shafts, it is often not possible to ensure that the  
18 formed bubbles are introduced into the riser tube. Further, the above mentioned system  
19 involves the pressurization of the foaming chamber. In such case an adequate seal around the  
20 impeller is needed in order to prevent leakage. Such seal is difficult to establish in situations  
21 where the impeller is introduced through the side of the molten metal bath.

22  
23 [0005] Thus, there exists a need for an improved impeller system for generating metal  
24 foam.

## 25 26 SUMMARY OF THE INVENTION

27 [0006] Thus, in one embodiment, the present invention provides a submerged gas  
28 discharge impeller for supplying a gas to liquid within a container, said impeller comprising:  
29 - a hollow shaft having at least one bore and a first end connected to a gas supply and  
30 a second end extending into said liquid through an opening in the bottom of said container;  
31 - the second end of said shaft including a gas discharge nozzle in fluid communication  
32 with said bore;

- 1 - the shaft including a seal for preventing leakage of said fluid;
- 2 - a drive means for rotating the shaft about its longitudinal axis.

3

4 [0007] In another embodiment, the invention provides a system for discharging a gas  
5 through a liquid, the system comprising:

- 6 - a container for said liquid, said container having a base with an opening;
- 7 - a hollow shaft having a first end connected to a gas supply and a second end  
8 extending into said liquid through said opening in said container;
- 9 - a gas discharge nozzle connected to said second end of said shaft;
- 10 - a seal provided adjacent said opening in said container for preventing leakage of said  
11 liquid;
- 12 - a motor connected to said shaft for rotating said shaft about its longitudinal axis.

13

14 [0008] In yet another embodiment, the invention provides a system for producing a metal  
15 foam from a molten metal comprising:

- 16 - a bath containing said molten metal, said bath comprising a container with an  
17 opening on the base thereof;
- 18 - a hollow, rotatable shaft extending generally vertically into said molten metal  
19 through said opening, said shaft including a first end extending into said molten metal and a  
20 second end connected to a gas supply;
- 21 - the first end of said shaft including a gas discharge nozzle submerged in said molten  
22 metal;
- 23 - a seal located between said shaft and said opening for preventing passage of said  
24 molten metal;
- 25 - a drive mechanism connected to said shaft for rotating said shaft about its  
26 longitudinal axis.

27

## 28 BRIEF DESCRIPTION OF THE DRAWINGS

29 [0009] These and other features of the preferred embodiments of the invention will  
30 become more apparent in the following detailed description in which reference is made to the  
31 appended drawings wherein:

32 [0010] Figure 1 is a cross sectional elevation of a metal foam casting apparatus.

1 [0011] Figure 2 is a cross sectional elevation of a detail of molten metal bath illustrating  
2 an impeller according to an embodiment of the present invention.

3 [0012] Figure 3 is a side view of a gas supply mechanism for the impeller of the  
4 invention.

5  
6 DESCRIPTION OF THE PREFERRED EMBODIMENTS

7 [0013] Figure 1 illustrates a metal foam casting system as taught in US application  
8 number 60/312,757, described above, in which the present invention can be used. As  
9 illustrated, the casting system includes a die 36 having a die cavity 38, which is fluidly  
10 connected to a riser tube 39. The riser tube 39 extends into a bath 32 containing a molten  
11 metal 34. The bath 32 also includes, at the base thereof, a porous plug, or nozzle, 44. A gas  
12 supply line 42, connected to the nozzle 44, introduces a gas through the nozzle 44, into the  
13 molten metal 34. Such gas leads to the formation of bubbles 46 which, due to their  
14 buoyancy, preferentially rise in the direction shown by the arrow C. As can be seen, by  
15 positioning the riser tube 39 generally directly over the nozzle 44, the bubbles are caused to  
16 enter such tube and rise to form a metal foam. As will be appreciated the opening of the tube  
17 39 may be provided with a funnel shaped end to assist in collecting the formed bubbles. The  
18 foam is, thereby, allowed to enter and fill the die cavity 38. As will be understood by persons  
19 skilled in the art, once the die cavity is filled with the metal foam, the die can be cooled to  
20 solidify the foam and, subsequently, remove the formed foam article.

21  
22 [0014] Figure 2 illustrates a rotating gas supply impeller for use, in one example, as an  
23 alternative to the stationary porous nozzle of the metal foam casting system described above  
24 and as illustrated in Figure 1.

25  
26 [0015] The rotating impeller according to one embodiment of the invention is shown  
27 generally at 100 in Figure 2. The impeller includes a hollow shaft 102 that extends generally  
28 vertically into the base 104 of the molten metal bath (not shown). As is commonly known in  
29 the art, the bath, including the base 104, is provided with a refractory or insulating material  
30 105 that is capable of withstanding the temperatures of the molten metal. A first, bottom end  
31 106 of the shaft 102 provides an exposed opening 108 into the hollow bore 110 of the shaft

1 102. Air is introduced into the bore 110 of the shaft 102 by connecting a gas supply line  
2 (discussed further below) to the opening 108.

3  
4 [0016] Turning briefly to Figure 3, an example of a gas supply arrangement is illustrated.  
5 As shown, the shaft 102 includes a threaded portion (not shown) on the interior wall of the  
6 bore 110. A rotary union 160 includes a threaded connector 162 having a thread that is  
7 complementary to that of the bore 110. The rotary union 160 is secured to the shaft 102 by  
8 screwing the connector 162 into to the bore 110. The rotary union 160 includes a rotating  
9 section 164 and a stationary section 166. The means of linking sections 164 and 166 together  
10 is commonly known and, indeed, the rotary union 160 itself is commercially available. A gas  
11 supply port 168 is provided on stationary section 166. A gas supply line 170 is then attached  
12 to the supply port 168. Although preferred gas supply system has been described, various  
13 other methods of providing a gas supply to the shaft 102 will be apparent to persons skilled in  
14 the art.

15  
16 [0017] Returning to Figure 2, on the second, top end 112 of the shaft 102, there is  
17 attached a gas outlet nozzle 114. The top end 112 of the shaft 102 extends into the molten  
18 metal bath through an opening 116, which extends through the base 104 and refractory  
19 material 105. A support 118 having a central bore 120 is provided in the opening 116 in the  
20 base 104. The shaft 102 extends through the central bore 120 of the support 118, with the  
21 central bore 120 being dimensioned to allow free rotation of the shaft 102. The support 118  
22 includes a generally conical upper portion 122, which includes an annular shoulder 124 that  
23 bears against a portion the inner surface 126 of the base 104, such portion being adjacent to  
24 the opening 116. The support 118 also includes a generally cylindrical body 117, through  
25 which extends the bore 120, the body 117 preferably extending through the opening 116.  
26 The outer diameter of the body 117 is preferably dimensioned to provide a snug fit within the  
27 opening 116. As indicated above, the upper portion 120 of the support 118 has a generally  
28 conical structure. Such structure aids in directing molten metal away from the shaft 102.  
29 Although the support 118 and the opening 116 are described in terms of preferred structural  
30 configurations, it will be understood by persons skilled in the art that various other  
31 geometries are possible within the scope of the present invention as described herein. It will  
32 also be understood that the support 118 is preferably made from a material that is capable of

1 withstanding the temperature of the molten metal. For example, suitable materials include  
2 alumina silicate, graphite or ceramics.

3  
4 [0018] The central bore 120 of support 118 includes an upper region 121, at the top end  
5 of the support 118, which has a larger diameter than that of the bore 120. Such widened  
6 diameter provides a ledge 128, which supports a seal or bushing 130. The bushing 130 has a  
7 generally cylindrical outer wall 132 that corresponds generally to the diameter of the upper  
8 region 121 of the support 118. In the preferred embodiment, the bushing 130 is maintained in  
9 position within the upper region 121 by frictional contact between its outer wall 132 and the  
10 inner wall of the upper region 121. Further, such arrangement ensures a tight seal between  
11 the bushing 130 and the support 118. In the preferred embodiment, the bushing 130 is made  
12 of graphite to withstand the temperatures of the molten metal to which it is exposed.  
13 However, other materials will be apparent to persons skilled in the art such as ceramics,  
14 metals, or composites. Some examples of possible materials for the bushing 130 include,  
15 *inter alia*, graphite, titanium diboride, tungsten, alumina, zirconium oxide ( $ZrO_2$ ), silicon  
16 carbide, silicon nitrate, boron nitrate, titanium carbide and tungsten carbide.

17  
18 [0019] In another embodiment, the support 118 can be integrally formed with the seal or  
19 bushing 130. However, it will be understood that a separate seal is preferred so as to  
20 facilitate replacement as the seal 130 wears out. It will also be understood that for forming an  
21 optimal seal, the underside of the nozzle 114 should be square with the upper contacting  
22 surface of the seal or bushing 130.

23  
24 [0020] In a preferred embodiment, the material chosen for the seal or bushing 130 is non-  
25 wetted by the molten metal. Similarly, the impeller or parts thereof is also made of a non-  
26 wetted material. In another embodiment, the elements in contact with the molten metal, i.e.  
27 the seal bushing 130, the support 118, the nozzle 114, and any other parts of the impeller,  
28 may be coated with a protective material that resists wetting by the molten metal and/or to  
29 seal the apparatus to prevent leakage.

30  
31 [0021] The bushing 130 also includes a central bore 134, which accommodates the upper  
32 end of the shaft 102 and allow for rotation of the shaft therein. The clearance between the



1 outer diameter of the shaft 102 and the bore 134 of the bushing 130 is preferably maintained  
2 as minimal as possible so as to provide a sealing arrangement there-between. In this manner,  
3 and with the seal between the bushing 130 and the support 118, leakage of molten metal  
4 within the bath is prevented.

5  
6 [0022] The gas discharge nozzle 114 preferably comprises a generally cylindrical body  
7 secured to the top end of the shaft. In the preferred embodiment, the body of the nozzle 114  
8 comprises a plurality of fins 115 extending radially from the central axis of the body. The  
9 nozzle 114 also includes a central opening 136 in fluid communication with the central bore  
10 108 of the shaft 102. In the preferred embodiment, the opening 136 does not extend through  
11 the entire body of the nozzle 114 and, instead, the body of the nozzle 114 is provided with  
12 one or more, and more preferably, a plurality of gas discharge vents 138 extending through  
13 the fins 115. The vents 138 radiate from, and are in fluid communication with, the opening  
14 136 of the nozzle 114. The vents 138 open into the molten metal bath so as to discharge the  
15 gas supplied through the shaft 102 into the molten metal. By securing the nozzle 114 to the  
16 shaft 102, it will be understood that rotation of the shaft 102 also results in the rotation of the  
17 nozzle. In the preferred embodiment, the bottom surface of the nozzle 114 abuts the top  
18 surface of the bushing 130 so as to establish a sealing arrangement there-between.

19  
20 [0023] The shaft 102 extends through an opening in a stationary support 140 located  
21 below the bath. The support 140 preferably includes a bearing 142 having a central bore 144  
22 that is greater in diameter than that of the shaft 102. The bore 144 is preferably provided  
23 with a bushing 146 through which is passed the shaft 102. It will be understood that the shaft  
24 102 is rotatably accommodated within the bushing 146. One of the purposes of the bearing  
25 142 is, as will be understood, to support and stabilize the shaft 102 while it is rotated. The  
26 bearing 142 is preferably also provided with a washer 148 on the bottom thereof, through  
27 which is passed the shaft 102. The purpose of the washer 148 is described below.

28  
29 [0024] At the bottom end 106 of the shaft 102, there is provided a collar 150, secured to  
30 the shaft. Between the collar 150 and the washer 148, there is provided a spring 152, the  
31 spring being in a compressed state. As will be understood, the spring, being provided in this  
32 manner, exerts a force bearing against the washer 148 and the collar 150, causing the washer

1 and the collar to be forced away from each other. This force will extend along the length of  
2 the shaft 102 thereby causing the bottom surface of the nozzle 114 to bear against the top  
3 surface of the bushing 130, thereby serving to strengthen the seal between the nozzle and the  
4 bushing to prevent leakage of molten metal from the bath. It will also be understood that  
5 such force will also ensure that the support 118 is pressed against the inner surface of the bath  
6 to ensure a seal there-between as well. It will be appreciated, however, that the primary  
7 reason for applying a force by means of the spring 152 is to seal the nozzle against the  
8 bushing. Although the use of a spring 152 is a preferred method of achieving the desired  
9 seal, it will be understood that any other means may also be employed. For example, the  
10 shaft 102 may be attached to any other force applying means to achieve the desired result.  
11 Alternatively, the weight of the shaft and associated elements may be sufficient to provide the  
12 necessary sealing force.

13  
14 [0025] The present invention envisages various means of rotating the shaft 102. In one  
15 embodiment, the shaft 102 is provided with a pulley 154, secured to the shaft 102 in a  
16 location along the length thereof. The pulley 154 translates a drive force applied thereto into  
17 axial rotation of the shaft 102. As is known in the art, the pulley 154 is adapted to engage a  
18 drive belt that is connected to a drive motor (not shown). In another embodiment, the pulley  
19 154 may be replaced with a sprocket that engages a cooperating sprocket on a drive shaft of a  
20 motor. The choice drive means for axially rotating the shaft 102 will depend upon the drive  
21 mechanism being used. It will also be understood that locating the drive means (for example  
22 the pulley 154) away from the bottom end 106 of the shaft 102 is preferred so as not to  
23 interfere with the gas supply line feeding the bore 108.

24  
25 [0026] In the preferred embodiment, a further bearing 156 is provided on the underside of  
26 the base 104 of the bath. The bearing 156 can be, for example, of the same structure as  
27 bearing 142 described above. It will be understood that the purpose of the bearing 156 is to  
28 support and stabilize the shaft 102 while it is rotated. It will also be understood that in other  
29 embodiments of the invention, the bearing 156 may not be needed if the shaft 102 is able to  
30 support itself. As shown, in the preferred embodiment of the invention, the bearing 156 is  
31 also provided with a bushing 157 similar to bushing 146. It will also be appreciated that any  
32 number of bearings or bushings can be used depending upon the needs of the apparatus.

1  
2 [0027] As described above, an impeller according to the present invention improves the  
3 dispersal of the gas discharged within the molten metal. Also, the impeller of the invention,  
4 by minimizing or eliminating the length of the shaft exposed to the molten metal, avoids  
5 damage thereto as described above as well as other deleterious effects of having a rotating  
6 shaft within the fluid molten metal. Also, by providing a means of discharging gas directly  
7 from the bottom of the bath, the desired vertical rise of the gas bubbles is achieved.

8  
9 [0028] In the above described embodiments, a system having a single impeller shaft and  
10 gas discharge nozzle has been described. However, the invention also contemplates other  
11 systems wherein several impellers and nozzles are employed. As will be apparent to persons  
12 skilled in the art, more than one impeller and nozzle combination may be more efficient when  
13 large diameter riser tubes 39 are used.

14  
15 [0029] The present invention has been described in terms of its use in a metal foam  
16 casting system. However, it will be appreciated that this is only one possible use of the  
17 invention and that various other uses are within the scope thereof. Although impeller speeds  
18 of around 4500 rpm are known in art of metal foam generation, any other desired speed  
19 would, of course, be possible.

20  
21 [0030] Although the invention has been described with reference to certain specific  
22 embodiments, various modifications thereof will be apparent to those skilled in the art  
23 without departing from the spirit and scope of the invention as outlined in the claims  
24 appended hereto.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE  
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**


1. A submerged gas discharge impeller for supplying a gas to liquid within a container, said impeller comprising:
  - a hollow shaft having at least one bore and a first end connected to a gas supply and a second end extending into said liquid through an opening in the bottom of said container;
  - the second end of said shaft including a gas discharge nozzle in fluid communication with said bore;
  - the shaft including a seal for preventing leakage of said fluid;
  - a drive means for rotating the shaft about its longitudinal axis.
2. The impeller of claim 1 wherein said liquid is a molten metal.
3. The impeller of claim 1 wherein said impeller is biased against said seal.
4. A system for discharging a gas through a liquid, the system comprising:
  - a container for said liquid, said container having a base with an opening;
  - a hollow shaft having a first end connected to a gas supply and a second end extending into said liquid through said opening in said container;
  - a gas discharge nozzle connected to said second end of said shaft;
  - a seal provided adjacent said opening in said container for preventing leakage of said liquid;
  - a motor connected to said shaft for rotating said shaft about its longitudinal axis.
5. The system of claim 4 wherein said liquid is a molten metal.
6. The system of claim 4 wherein said impeller is biased against said seal.
7. A system for producing a metal foam from a molten metal comprising:
  - a bath containing said molten metal, said bath comprising a container with an opening in the base thereof;

- a hollow, rotatable shaft extending generally vertically into said molten metal through said opening, said shaft including a first end extending into said molten metal and a second end connected to a gas supply;
- the first end of said shaft including a gas discharge nozzle submerged in said molten metal;
- a seal located between said shaft and said opening for preventing passage of said molten metal;
- a drive mechanism connected to said shaft for rotating said shaft about its longitudinal axis.

8. The system of claim 4 wherein said impeller is biased against said seal.
9. The system of claim 8 wherein said impeller is associated with a spring for biasing said impeller against said seal.
10. The system of claim 7 wherein portions of said system in contact with said molten metal are formed of a material that repels said molten metal.
11. The system of claim 7 wherein portions of said system in contact with said molten metal are coated with a material that repels said molten metal.


1/3

Figure 1




2 / 3

Figure 2



3/3

Figure 3





## INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 03/00292

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B01F3/04 B01F7/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 127 610 A (NORSK HYDRO AS) 29 August 2001 (2001-08-29) the whole document	1-8, 10, 11
Y	---	9
X	US 6 146 443 A (ECKERT C EDWARD) 14 November 2000 (2000-11-14) the whole document	1, 4, 7
A	---	
A	US 3 346 033 A (STANISLAW OLEJNICZAK JERZY) 10 October 1967 (1967-10-10) the whole document	1-11
Y	---	
Y	US 4 850 723 A (WHITEMAN JR MARVIN E) 25 July 1989 (1989-07-25) abstract; figure 1	9
	-----	

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

24 June 2003

Date of mailing of the international search report

03/07/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Muller, G

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 03/00292

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1127610	A	29-08-2001	NO 20000974 A	27-08-2001
			AU 2311501 A	30-08-2001
			CA 2338110 A1	25-08-2001
			EP 1127610 A2	29-08-2001
			JP 2001262244 A	26-09-2001
			NZ 510051 A	28-09-2001
			PL 346086 A1	27-08-2001
			SI 20463 A	31-08-2001
			SK 2552001 A3	08-10-2001
			US 2001017434 A1	30-08-2001
US 6146443	A	14-11-2000	US 6143055 A	07-11-2000
			US 6162279 A	19-12-2000
			US 6066289 A	23-05-2000
			US 5968223 A	19-10-1999
			US 6299828 B1	09-10-2001
			US 2001020760 A1	13-09-2001
			US 6217631 B1	17-04-2001
			US 6521015 B1	18-02-2003
US 3346033	A	10-10-1967	GB 1072869 A	21-06-1967
			DE 1519627 A1	01-10-1970
			FR 1469902 A	17-02-1967
			NL 6602280 A	24-08-1966
US 4850723	A	25-07-1989	NONE	